

Product Specification

Product No: KERSAD2022026

Product model: SAD1010S

File No: KER2022001

Version No: V2.0

Date: 2022-01-01

Index


01	Product Features		2
02	Application		2
03	Specification		3-4
04	Instructions and Aft	er-Sales Service ·····	4



Product Features

- 1. Auto power on / off at a scheduled time;
- 2. Loop Video;
- 3. Wireless WiFi or 4G;
- 4. CMS Real Time Update;
- 5. 178/178 full view angle;
- 6. Support 1920*1080p video;
- 7. VESA Standard Wall Shelf Mount;
- 8. 3rd party applications pre-installed;
- 9. Integrated Android 6.0/8.1/11.0 rooted Solution;
- 10. Customized Solutions Satisfy Your Multiple Advertising Needs;
- 11. With CE FCC ROHS certification;

Application



Specification



supermarket, airport, hospital and any commercial and public in-store environment.

10.1 inch Android Based Enclosed Video Screen





Description

- Model No.: SAD1010S.
- Android based, support 3rd party APK, to install via USB/SD card.
- Enclosed design, easy to mount on display shelf.
- With WiFi and Internet.

Product Technical Specification

Model	SAD1010S	Shell color	Standard: black
Open Frame or Enclosed	Enclosed	External Port	Support SD/U flash disk
LCD Panel	10.1 inch	Input	AC 100-240V
Resolution	1280*800	Output	DC 12V/2A
Display Ratio	16:9	Power consumption (Watt)	≤12W
Brightness	220cd/m2	Standby (Watt)	≤1W
Contrast	500:1	Material	ABS material injection process
Colour	16.7M	Installation	75*75mm VESA Wall Mount
Visible Angle	178/178	Image Format	JPEG/BMP/GIF/PNG
Response Time	5ms	Life Time (hrs)	>50000 H
Audio Format	MP3/ WMA/WAV	Video Format	MPEG1/MPEG2/MP4, AV/MOV/3GP/RMVP/MKV
Visible Area	216.96×135.6mm(H×V)	Control Method	Remote control/Mouse
Outline dimension	252.05*174.05*27.6mm	Default Language	English
СРИ	A83-Eight Core 2.0GHz/RK3288-Four Core-1.8Hz/RK3568-Four Core-2.0Hz	Menu Language	Support Chinese, English
os	Android 6.0/8.1/11.0	Memory (RAM)	2GB
03		ROM NAND flash	8GB/16GB
Storage Temperature	0℃~40℃	Working Temperature	-20℃~60℃
Working Humidity	20%-80%RH	Storage Humidity	10%-75%
Decoded Resolution	Support 1080P	RTC Real-time Clock	Support
Product Weight (N.W.)	1.2kg	Switch Time Setting	Support
System Update	SD card update	Plug Types	US, EU, AU, UK Optional
Package Size	A single package: 492*76*279mm Bulk packages:	Packaging	16pcs/Package Package Weight: 25kg (Reference Only)

	784*516*250mm		
External Interface	DC IN/USB*2/HDMI OUT/SD/Earphone	Speaker	Size: 22MM*74MM, speakers 8R 2W
Touch Panel	Support	External Port	Support SD/U flash disk
Accessories	User Guide, Instruction Book, Warranty, Desiccant	Optional	

Accessories: instruction manual, warranty card, desiccant, certificate, power adapter;

Notes: Some of the above specifications are optional for reference only. Please select the relevant function parameters according to your need and confirm the parameters with our sales team. The final interpretation right belongs to Shenzhen Kerchan Technology Co., Ltd. A corresponding fee will be charged according to the optional function, so please confirm with us.

Instructions and After-Sales Service

Instructions

- 1. The working voltage: $100V 240V \sim 50/60Hz$ AC, please do not exceed the working voltage range.
- 2. Please place gently and do not stress when shipping and storing.

Warranty and After-Sales Service

- ${\bf 1.}\ \ {\bf Please}\ {\bf read}\ {\bf carefully}\ {\bf the}\ {\bf product}\ {\bf specifications}\ {\bf firstly}\ .$
- 2. Before using, please confirm the product not been damaged in the transport, if damaged, it cannot be installed
- 3. The power supply in the package is only used for this product; Do not use other power source.
- 4. When the product is faulty, please entrust the professional person to carry out inspection and maintenance to ensure the safety. Do not disassemble by yourself to avoid unnecessary damage.
- 5. To prevent to be suffocated to death, package materials should be stay away from children.
- 6. To prevent to be swallowed by children, please take care of the small components.
- 7. Do not cover anything on the product.
- 8. Products should be away from the strong magnetic field interference and high temperature objects.