

Product Specification

Product No: KERSAD2022062

Product model: SAD2150PJ

File No:KER2022001

Version No: V2.0

Date: 2022-01-01



Index

01	•	Product Features	2
02	•	Application	2
03	•	Specification	3
04		Instructions and After-Sales Service	4



Product Features

1.Full view angle;

- 2.Support HDMI input;
- 3.Boot or shutdown per designed schedule;
- 4. Individual display or connect & synchronize mode;
- 5.Unique sizes can be customized;
- 6.With CE FCC ROHS certification;

Application

21.5 inch Video Wall Screen Display is a great way to advertise your product or service in retail P.O.P. or P.O.S environments by displaying with your custom videos to boost your sales and bring a better shopping experience for your customers, which is widely used in retail stores, restaurants, bank, supermarket, airport, hospital and any commercial and public in-store environment.

25.1 inch Video Wall Screen Display



Description

- Model No.: SAD2150PJ.
- Support HDMI input.
- Horizontal or vertical installation.



Product Technical Specification

		.	a
Model	SAD2150PJ	Shell color	Standard: black
Open Frame or Enclosed	Enclosed	Input	AC 100-240V
LCD Panel	21.5 inch	Output	DC 12V/2A
Resolution	1920*1080	Power consumption (Watt)	≤17W
Brightness	250cd/m2	Standby (Watt)	≤1W
Contrast	1000:1	Material	ABS material injection process
Display Ratio	16:9	Speaker	Size: ⌀ 45MM, speakers 8R 1W*2
Colour	16.7M	Installation	75*75VESA Wall Mount
Response Time	8ms	Life Time (hrs)	>50000 H
Visible Angle	178/178	Image Format	JPEG/BMP/GIF/PNG
Audio Format	MP3/ WMA/WAV	Video Format	MPEG1/MPEG2/MP4, AV/MOV/3GP/RMVP/MKV
Visible Area	476.06*267.79mm	Control Method	Remote control/Mouse
Outline dimension	484.5*284.4*34.3mm	Default Language	English
CPU	TSUMV59XU	Menu Language	Support Chinese, English
Storage Temperature	0°C~40°C	Working Temperature	-20℃~60℃
Working Humidity	20%-80%RH	Storage Humidity	10%-75%
Decoded Resolution	Support 1080P	RTC Real-time Clock	Support
Product Weight (N.W.)	2.6kg	Switch Time Setting	Support
System Update	U flash disk update	Plug Types	US, EU, AU, UK Optional
Package Size	A single package: 632*72*430mm Bulk packages: 629*196*426mm	Packaging	3pcs/Package Package Weight: 11kg (Reference Only)
External Interface	DC IN/DC-SW/ Earphone*4/HDMI in/SD/USB	External Port	Support SD/U flash disk
Touch Panel	Support	Accessories	User Guide, Instruction Book, Warranty, Desiccant



Accessories: instruction manual, warranty card, desiccant, certificate, power adapter;

Notes: Some of the above specifications are optional for reference only. Please select the relevant function parameters according to your need and confirm the parameters with our sales team. The final interpretation right belongs to Shenzhen Kerchan Technology Co., Ltd. A corresponding fee will be charged according to the optional function, so please confirm with us.

Instructions and After-Sales Service

Instructions

- 1. The working voltage: 100V 240V ~ 50/60Hz AC, please do not exceed the working voltage range.
- 2. Please place gently and do not stress when shipping and storing.

Warranty and After-Sales Service

1. Please read carefully the product specifications firstly .

2. Before using, please confirm the product not been damaged in the transport, if damaged, it cannot be installed.

- 3. The power supply in the package is only used for this product; Do not use other power source.
- 4. When the product is faulty, please entrust the professional person to carry out inspection and maintenance to ensure the safety. Do not disassemble by yourself to avoid unnecessary damage.
- 5. To prevent to be suffocated to death, package materials should be stay away from children.
- 6. To prevent to be swallowed by children, please take care of the small components.
- 7. Do not cover anything on the product.
- 8. Products should be away from the strong magnetic field interference and high temperature objects.